

# 200 Speedster®

An aggressive, agile beast with a 0-30 mph (48.28 kph) acceleration time of 2.9 seconds\* and a 65-mph (104.60 kph) top speed. Room for up to seven adrenaline junkies.

MUSCLECRAFT | 2011



\*Based on internal BRP testing under similar conditions.



Bright White



## CLCS Specifications

### DIMENSIONS

Length	19' 9" / 6.02 m
Beam	8' / 2.44 m
Draft	12" / 30.5 cm
Dry weight: No tower	2,770 lb. / 1,256 kg
With tower	2,830 lb. / 1,284 kg
Seating capacity	7
Fuel capacity	44 gal. / 166.5 l

### ENGINE

Model	1503 Rotax® 4-TEC® (x 2)
Type	Twin 1.5 l high output

## Highlights

- Twin 1.5 l high output Rotax 4-TEC engine
- Swim platform with 2-step ladder
- Dual stern storage compartment
- Sundeck pad
- Pop-up ski pylon
- Cockpit courtesy lights
- Ski storage
- Satellite-ready AM/FM/CD stereo with MP3 port and 4 speakers
- Depth finder
- 12 volt jack
- Windscreen with pop-up wind deflector and helm storage
- Built-in cooler
- Multi-function aluminum black rails
- Grab handles
- On-board storage



Twin Rotax engines



Large cockpit area



Full instrumentation dash



Stern storage access

## Overall Specifications

### DIMENSIONS

Length	19' 9" / 6.02 m
Beam	8' / 2.44 m
Draft	12" / 30.5 cm
Dry weight: No tower	2,770 lb. / 1,256 kg
With tower	2,830 lb. / 1,284 kg
Storage capacity	46 cu. ft. / 1.3 cu m
Seating capacity	7
Weight capacity	1,365 lb. / 619 kg
Fuel capacity	44 gal. / 166.5 l

### DIMENSIONS (ON TRAILER)

Length [tongue folded]	22' 7" / 6.88 m [20' 6" / 6.25 m]
Width	8' 6" / 2.59 m
Height: No tower	6' 6" / 1.98 m
Tower down	7' 1" / 2.16 m
Tower up	9' 11" / 3.02 m
Gross weight: No tower	4,095 lb. / 1,857 kg
With tower	4,115 lb. / 1,885 kg

### ENGINE

Model	Fuel injected, 1503 Rotax 4-TEC (2)
Displacement	1,494 cc
Type	Twin 1.5 l high output
Cylinders (/engine)	3
Max RPM (/engine)	8,000
Octane: Minimum	87
Recommended	91
Emission level	CARB 3-Star
Cooling system	Closed-Loop Cooling System



Bright White

### ELECTRICAL

Generator	30 amp / 380 W
Battery	12 V

### HULL & DECK

Material	Composite FRP
Vinylester barrier layer	Std
Full fiberglass stringer	Std
Graphics	Std
Deadrise	21°
Color	Bright White

### PROPULSION

Jet pump type:	
Axial flow	Single stage
Pump diameter	6 1/4" / 15.63 cm
Impeller:	
Material	Stainless steel
Outside diameter (mm)	159 ± .07
Reverse system	Std

## Equipment

### HULL & DECK

- Cleats – chrome (6)
- Cup holders (6)
- Rub rail – Black
- Grab handles (8)
- Non-skid decking
- Navigation lights – bow side
- Courtesy lights (3)
- Ski pylon – pull-up
- Tow hooks – stainless steel bow & stern
- Reboarding ladder – stern (2-step)
- Engine access
- Engine blower (2)
- Auto bilge pump

### STORAGE

- Anchor
- In-floor, lockable
- Under seat
- Sunpad, lockable
- Glove box, lockable

### CONTROL STATION

#### HELM

- Steering – custom
- Steering – rack & pinion
- Horn
- Separated shift & dual throttle levers
- Battery switch
- **Neutral lock\***
- Fuse box
- Security system D.E.S.S. magnetic lanyard key

#### INSTRUMENTATION

- Gauges – backlight & anti-fog
- Fuel level
- Tachometer
- Speedometer
- Depth finder
- Overheat

### COCKPIT

- Dash finish – Pearlstone
- Outlet – 12 volt accessory (1)
- Cooler – integrated

### SEATING

#### Driver Seat

- Track & swivel

#### Passenger Seat

- Track & swivel

### STEREO & SOUND

- Stereo system – satellite-ready
- Speakers – cockpit (4)
- MP3 port

### CANVAS & MISCELLANEOUS

- Sunpad
- Wind deflector
- Warranty (1 yr)

### CERTIFICATIONS

- NMMA
- CMMA

### TRAILER

- Single axle
- Disc brakes
- Swing-away tongue

## Options

- Wakeboard tower & racks
- Carpet – snap-in
- Mirror – with tower only
- Mooring cover
- Bimini top
- Galvanized trailer with disc brakes
- Fire extinguisher
- Anchor
- Warranty – B.E.S.T. (3 years)



\*New for 2011